

View Online at <https://aerobasegroup.com/nsn/5320-00-151-5481>

Thread Class:

3a

Thread Direction:

Right-hand

Identification Code Color:

Bronze

Fastener Length:

Between 1.187 inches and 1.207 inches

Head Style:

Err-090

Head Height:

Between 0.093 inches and 0.105 inches

Width Between Flats:

Between 0.190 inches and 0.193 inches

Shank Diameter:

Between 0.436 inches and 0.437 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.641 inches and 0.676 inches

Grip Length:

0.567 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.438 inches

Shear Strength:

95000 single pounds per square inch

Material:

Steel comp 8740 or steel comp 4140 or steel comp e4340 or steel comp 4340

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-5000 military specification 3rd material response or mil-s-5000 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.