## NSN 5320-00-151-5503

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-151-5503



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 2.250 inches and 2.270 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.093 inches and 0.105 inches

#### Width Between Flats:

Between 0.190 inches and 0.193 inches

#### Shank Diameter:

Between 0.436 inches and 0.437 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.641 inches and 0.676 inches

### Lubrication:

Cetyl alcohol

## Grip Length:

1.630 inches

## Thread Size:

0.438 inches

## Shear Strength:

125000 single pounds per square inch

#### Material:

Steel comp 431

### **Material Specification:**

Mil-s-18732 military specification single material response

### Surface Treatment:

Cadmium and chromate

### Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-00-151-5503

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

