## NSN 5320-00-157-6988

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-157-6988 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 1.370 inches and 1.390 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.078 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.475 inches and 0.505 inches **Grip Length:** 1.005 inches Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 50.0 rockwell c and 55.0 rockwell c **Thread Size:** 0.312 inches **Shear Strength:** 156000 single pounds per square inch Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium or chromate **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5320-00-157-6988

Pin-rivet - Page 2 of 2



Fiig:

A528u0