# NSN 5320-00-157-6988

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-157-6988



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.370 inches and 1.390 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.068 inches and 0.078 inches

### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3110 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.475 inches and 0.505 inches

# Grip Length:

1.005 inches

Min. Tensile Strength (psi):

260000 pounds per square inch

### Hardness Rating:

50.0 rockwell c and 55.0 rockwell c

### **Thread Size:**

0.312 inches

### Shear Strength:

156000 single pounds per square inch

### Material:

Steel comp h11

### Material Specification:

Ams 6487 assn standard single material response

#### Surface Treatment:

Nickel and cadmium or chromate

### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-00-157-6988

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

