## NSN 5320-00-160-2351

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-160-2351

Fastener Length:
0.592 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.162 inches and 0.164 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
0.333 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.406 inches and 0.470 inches
Min. Tensile Strength (psi):
112000 pounds per square inch
Hardness Rating:
32.0 rockwell c and 53.0 rockwell c
Shear Strength:
2340 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp 4027 or steel comp 4037 or steel comp 4130 body
Material Specification:
Qq-w-405 federal specification all material responses or mil-s-6758 military specification all material responses body
Surface Treatment:
Cadmium and chromate body
Surface Treatment Specification:
Qq-p-416 type 2, cl 2 federal specification single treatment response body
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-s-6049 spec.