## NSN 5320-00-160-2505

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-160-2505



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.510 inches and 1.530 inches

### Head Style:

Err-090

#### Head Height:

Between 0.080 inches and 0.090 inches

## Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2485 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.415 inches and 0.440 inches

## Lubrication:

Cetyl alcohol

## Grip Length:

1.130 inches

## Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

## Shear Strength:

125000 single pounds per square inch

## Material:

Steel comp 431

## **Material Specification:**

Mil-s-18732 military specification single material response or ams 5628 assn standard single material response

#### Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-00-160-2505

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

