

View Online at <https://aerobasegroup.com/nsn/5320-00-160-2699>

Fastener Length:

0.928 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.197 inches and 0.199 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.386 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.719 inches and 0.782 inches

Min. Tensile Strength (psi):

112000 pounds per square inch

Hardness Rating:

48.0 rockwell c and 53.0 rockwell c stem

Shear Strength:

3450 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4027 or steel comp 4037 or steel comp 4130 sleeve

Material Specification:

6 federal standard all material responses or astm a547 assn standard 2nd material response or mil0s06758 military specification 3rd material response sleeve

Surface Treatment:

Cadmium and chromate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

spec.