

View Online at <https://aerobasegroup.com/nsn/5320-00-160-2856>

Fastener Length:

0.967 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.162 inches and 0.164 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.333 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.781 inches and 0.845 inches

Min. Tensile Strength (psi):

112000 pounds per square inch

Hardness Rating:

48.0 rockwell c and 53.0 rockwell c stem

Shear Strength:

2340 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4027 or steel comp 4037 or steel comp 4130 sleeve

Material Specification:

Astm a547 assn standard single material response or mil-s-6049 military specification single material response stem

Surface Treatment:

Cadmium and chromate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.