# NSN 5320-00-160-3209

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-160-3209

# Fastener Length:

0.303 inches

## Head Style:

Straight pan

# Head Height:

Between 0.125 inches and 0.135 inches

## Shank Diameter:

Between 0.197 inches and 0.199 inches

#### Shank Style:

Self-plugging mechanically locked stem

### Head Major Diameter:

Between 0.305 inches and 0.332 inches

### Expansion Device:

Serrated stem-type w

#### Grip Length:

Between 0.094 inches and 0.157 inches

#### Min. Tensile Strength (psi):

112000 pounds per square inch

### Hardness Rating:

48.0 rockwell c and 53.0 rockwell c stem

## Shear Strength:

3450 single pounds per square inch

### Material:

Steel comp 4027 or steel comp 4037 or steel comp 4130 sleeve

### **Material Specification:**

Astm a547 assn standard single material response or mil-s-6049 military specification single material response stem

### Surface Treatment:

Cadmium and chromate sleeve

### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

#### Shelf Life:

N/a

# Unit Of Measure:

```
--
```

### Demilitarization:

No

Fiig:

A040a0

## Mil-std (military Standard):

Mil-s-6758 spec.