NSN 5320-00-160-3215



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-00-160-3215 **Fastener Length:** 0.428 inches **Head Style:** Straight pan **Head Height:** Between 0.125 inches and 0.135 inches **Shank Diameter:** Between 0.197 inches and 0.199 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** Between 0.305 inches and 0.332 inches **Expansion Device:** Serrated stem-type w **Grip Length:** Between 0.219 inches and 0.282 inches Min. Tensile Strength (psi): 112000 pounds per square inch **Hardness Rating:** 48.0 rockwell c and 53.0 rockwell c stem **Shear Strength:** 3450 single pounds per square inch Material: Steel comp 4027 or steel comp 4037 or steel comp 4130 sleeve **Material Specification:** 66 federal standard 1st material response or astm a547 assn standard 2nd material response or 66 federal standard 3rd material response or mil-s-6758 military specification 3rd material response sleeve **Surface Treatment:** Cadmium and chromate sleeve **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response stem Shelf Life: N/a **Unit Of Measure:** Demilitarization: No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.