

View Online at <https://aerobasegroup.com/nsn/5320-00-160-3254>

**Fastener Length:**

1.030 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.162 inches and 0.164 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

0.333 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.844 inches and 0.907 inches

**Min. Tensile Strength (psi):**

112000 pounds per square inch

**Hardness Rating:**

48.0 rockwell c and 53.0 rockwell c stem

**Shear Strength:**

2340 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Steel comp 4027 or steel comp 4037 or steel comp 4130 sleeve

**Material Specification:**

66 federal standard 1st material response or astm a547 assn standard 2nd material response or 66 federal standard 3rd material response or mil-s-6758 military specification 3rd material response sleeve

**Surface Treatment:**

Cadmium and chromate sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.