## NSN 5320-00-164-1219

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-164-1219 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.627 inches and 0.647 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: Between 0.079 inches and 0.081 inches **Shank Diameter:** Between 0.189 inches and 0.190 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.295 inches and 0.315 inches Lubrication: Cetyl alcohol **Grip Length:** 0.317 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-00-164-1219

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0