

View Online at <https://aerobasegroup.com/nsn/5320-00-165-0134>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.197 inches and 1.217 inches

**Head Height:**

Between 0.077 inches and 0.090 inches

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

0.2641 mils and 0.2651 centimeters

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

0.415 mils and 0.440 centimeters

**Lubrication:**

Cetyl alcohol

**Grip Length:**

0.817 centimeters

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.250 inches

**Shear Strength:**

10490 double pounds per square inch

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 4340 or steel comp e4340

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-5000 military specification 3rd material response or mil-s-5000 military specification 4th material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5626 spec.