

View Online at <https://aerobasegroup.com/nsn/5320-00-165-0134>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.197 inches and 1.217 inches

Head Height:

Between 0.077 inches and 0.090 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

0.2641 mils and 0.2651 centimeters

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

0.415 mils and 0.440 centimeters

Lubrication:

Cetyl alcohol

Grip Length:

0.817 centimeters

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

10490 double pounds per square inch

Material:

Steel comp 4140 or steel comp 8740 or steel comp 4340 or steel comp e4340

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-5000 military specification 3rd material response or mil-s-5000 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.