## NSN 5320-00-165-8737

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-165-8737

| Fastener Length:  |
|---|
| Between 0.990 inches and 1.010 inches                       |
| Head Style:   |
| Universal   |
| Head Height:  |
| Between 0.054 inches and 0.064 inches                       |
| Shank Diameter:   |
| Between 0.124 inches and 0.128 inches                       |
| Shank Style:  |
| Straight  |
| Head Major Diameter:  |
| Between 0.238 inches and 0.262 inches                       |
| Grip Length:  |
| Between 0.802 inches and 0.822 inches                       |
| Shear Strength:   |
| 37000 single pounds per square inch                         |
| Material:   |
| Aluminum alloy 2024   |
| Material Specification:                                     |
| Qq-a-430 federal specification single material response     |
| Surface Treatment:  |
| Anodize   |
| Surface Treatment Specification:                            |
| Mil-c-5541 military specification single treatment response |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A040a0  |
| Mil-std (military Standard):                                |
| Mil-c-5541 spec.  |
|   |