

View Online at <https://aerobasegroup.com/nsn/5320-00-165-8775>

Fastener Length:

Between 0.240 inches and 0.260 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.155 inches and 0.159 inches

Shank Style:

Straight w/radius chamfered tip

Head Major Diameter:

Between 0.282 inches and 0.290 inches

End Application:

W/s: aircraft, t-38; aircraft (ac-130h, mc-130h, ec-130e, hc-130); aircraft, awacs, e-3a; aircraft, galaxy c-5; aircraft, stratofortress b-52; aircraft, f-111; aircraft, phantom f-4; aircraft, stratolifter c-135; aircraft, b-2 bomber (atb)

Grip Length:

Between 0.006 inches and 0.026 inches

Shear Strength:

24000 single pounds per square inch

Countersink Angle:

Between 99.5 degrees and 100.5 degrees

Material:

Aluminum alloy 5056

Material Specification:

Qq-a-430 federal specification single material response

Surface Treatment:

Anodize or oxide film

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.