

View Online at <https://aerobasegroup.com/nsn/5320-00-165-8775>

**Fastener Length:**

Between 0.240 inches and 0.260 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.155 inches and 0.159 inches

**Shank Style:**

Straight w/radius chamfered tip

**Head Major Diameter:**

Between 0.282 inches and 0.290 inches

**End Application:**

W/s: aircraft, t-38; aircraft (ac-130h, mc-130h, ec-130e, hc-130); aircraft, awacs, e-3a; aircraft, galaxy c-5; aircraft, stratofortress b-52; aircraft, f-111; aircraft, phantom f-4; aircraft, stratolifter c-135; aircraft, b-2 bomber (atb)

**Grip Length:**

Between 0.006 inches and 0.026 inches

**Shear Strength:**

24000 single pounds per square inch

**Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

**Material:**

Aluminum alloy 5056

**Material Specification:**

Qq-a-430 federal specification single material response

**Surface Treatment:**

Anodize or oxide film

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.