## NSN 5320-00-165-8799

Solid Rivet - Page 1 of 2

A040a0



view Online at https://aerobasegroup.com/nsn/5320-00-165-6799
Identification Code Color:
Natural
Fastener Length:
Between 1.740 inches and 1.760 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Head Height:
0.042 inches
Shank Diameter:
Between 0.124 inches and 0.128 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
Between 0.221 inches and 0.229 inches
Grip Length:
1.552 mils and 1.572 centimeters
Shear Strength:
41000 single pounds per square inch
Countersink Angle:
Between 99.5 degrees and 101.5 degrees
Heat Treatment:
T-73 solution heat treated
Material:
Aluminum alloy 7050
Material Specification:
Qq-a-430, t73 uns a97050 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2, class 1 military specification single treatment response
Specification Data:
96906-ms20426 government standard and 88044-an426/canceled/ government standard
Specification Or Standard:
2024 composition and t4 condition
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

## NSN 5320-00-165-8799

Solid Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.