

View Online at <https://aerobasegroup.com/nsn/5320-00-170-3011>

Fastener Length:

1.365 inches

Head Style:

Straight pan

Head Height:

Between 0.125 inches and 0.135 inches

Shank Diameter:

Between 0.197 inches and 0.199 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.305 inches and 0.332 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 1.156 inches and 1.220 inches

Min. Tensile Strength (psi):

112000 pounds per square inch

Hardness Rating:

48.0 rockwell c and 53.0 rockwell c stem

Shear Strength:

3450 single pounds per square inch

Material:

Steel comp 4027 or steel comp 4037 or steel comp 4130 sleeve

Material Specification:

66 federal standard 1st material response or astm a547 assn standard 2nd material response or 66 federal standard 3rd material response or mil-s-6758 military specification 4th material response sleeve

Surface Treatment:

Cadmium and chromate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.