NSN 5320-00-172-7275

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-172-7275

Fastener Length:

0.850 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.186 inches and 0.190 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.349 inches and 0.357 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.626 inches and 0.687 inches

Shear Strength:

1090 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Heat Treatment:

H-38 strain hardened locking ring

Material:

Aluminum alloy 5056 locking ring

Material Specification:

Qq-a-430 federal specification single material response locking ring

Surface Treatment:

Chromate stem

Surface Treatment Specification:

Mil-c-5541 military specification 1st treatment response stem

Specification Data:

80205-nas1399 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.