

View Online at <https://aerobasegroup.com/nsn/5320-00-175-7605>

Fastener Length:

Between 0.552 inches and 0.592 inches

Head Style:

Universal

Head Height:

Between 0.067 inches and 0.077 inches

Shank Diameter:

Between 0.154 inches and 0.158 inches

Shank Style:

Drive pin

Head Major Diameter:

Between 0.296 inches and 0.328 inches

Expansion Device:

Drive stem-type h

Grip Length:

Between 0.422 inches and 0.453 inches

Heat Treatment:

T-4 solution heat treated

Material:

Steel comp 301 stem or steel comp 302 stem or steel comp 303 stem or steel comp 303f stem or steel comp 303s stem or steel comp 303se stem or steel comp 304 stem or steel comp 304l stem or steel comp 305 stem or steel comp 308 stem or steel comp 309 stem or steel comp 309s stem or steel comp 310 stem or steel comp 310s stem or steel comp 314 stem or steel comp 316 stem or steel comp 316l stem or steel comp 317 stem or steel comp 321 stem or steel comp 323 stem or steel comp 324 stem or steel comp 347 stem or steel comp 348 stem or steel comp 385 stem

Material Specification:

Qq-a-430 federal specification single material response body

Surface Treatment:

Passivate stem

Surface Treatment Specification:

Qq-p-35 federal specification all treatment responses stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.