# NSN 5320-00-178-8713

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-178-8713



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.697 inches and 0.717 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.059 inches and 0.069 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2485 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.387 inches and 0.412 inches

### Lubrication:

Cetyl alcohol

# Grip Length:

0.317 inches

# Thready Qty Per Inch (tpi):

28

### Thread Size:

0.250 inches

## Shear Strength:

95000 single pounds per square inch

#### Material:

Titanium alloy

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

294, fscm 73197 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5320-00-178-8713

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

