

View Online at <https://aerobasegroup.com/nsn/5320-00-181-5993>

Fastener Length:

Between 1.288 inches and 1.318 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.197 inches and 0.199 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.386 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 1.094 inches and 1.157 inches

Hardness Rating:

32.0 rockwell c and 53.0 rockwell c

Shear Strength:

3450 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4037 stem or steel comp 4130 stem or steel comp 4027 stem or steel comp 8630 stem

Material Specification:

66 federal standard all material responses stem or mil-s-8758 military specification 1st material response stem or mil-s-6050 military specification 2nd material response stem

Surface Treatment:

Cadmium stem

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-s-8758 spec.