NSN 5320-00-181-6809

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-181-6809 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.280 inches and 1.300 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.081 inches **Shank Diameter:** Between 0.189 inches and 0.190 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.258 inches and 0.305 inches **Grip Length:** 1.005 inches Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 50.0 rockwell c and 55.0 rockwell c **Thread Size:** 0.190 inches **Shear Strength:** 156000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response **Surface Treatment:** Cadmium and chromate or nickel and cadmium **Surface Treatment Specification:** Qq-p-416 type 2, cl 2 federal specification single treatment response or ams2416 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-00-181-6809

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0