## NSN 5320-00-182-6885

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-182-6885 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.802 inches and 0.822 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0635 inches and 0.0645 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2564 inches and 0.2612 inches Lubrication: Cetyl alcohol **Grip Length:** 0.505 inches **Thread Size:** 0.164 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** 294, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-00-182-6885

Pin-rivet - Page 2 of 2



Fiig:

A528u0