NSN 5320-00-182-6888

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-182-6888 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 0.750 inches and 0.775 inches **Head Style:** Err-090 **Head Height:** Between 0.039 inches and 0.049 inches **Shank Diameter:** 0.1881 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.280 inches and 0.290 inches Tip Diameter: 0.1793 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.490 inches and 0.505 inches Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.164 inches **Shear Strength:** 108000 single pounds per square inch Material: Steel comp 8740 or steel comp 4340 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

--**Demilitarization:** No

NSN 5320-00-182-6888

Pin-rivet - Page 2 of 2



Fiig:

A528u0