NSN 5320-00-185-0898

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-185-0898

н	eac	15	tvi	Δ.
	cal	ı	LVI	┖.

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.258 inches and 0.260 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.463 inches and 0.507 inches

Expansion Device:

Threaded stem

Grip Length:

Between 0.407 inches and 0.469 inches

Hardness Rating:

30.0 rockwell c and 45.0 rockwell c

Shear Strength:

7200 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Self locking

Material:

Iron alloy 660 stem

Material Specification:

Ams 5735sjgbams 5737 assn standard single material response sleeve

Surface Treatment:

Passivate stem

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response stem

Specification Data:

80205-nas1672 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0