NSN 5320-00-191-4179

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-191-4179

| Small pan Head Height: Between 0.135 inches and 0.151 inches Shank Diameter: Between 0.244 inches and 0.253 inches Shank Style: Straight Head Major Diameter: Between 0.414 inches and 0.444 inches Grip Length: Any acceptable Heat Treatment: Annealed Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1011 or steel comp 1020 or steel comp 1021 or steel comp 1021 or steel comp 1022 Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
|--|-----|
| Head Style: Small pan Head Height: Between 0.135 inches and 0.151 inches Shank Diameter: Between 0.244 inches and 0.253 inches Shank Style: Straight Head Major Diameter: Between 0.414 inches and 0.444 inches Grip Length: Any acceptable Heat Treatment: Any acceptable or steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1021 or steel comp 1022 Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
| Head Height: Between 0.135 inches and 0.151 inches Shank Diameter: Between 0.244 inches and 0.253 inches Shank Style: Straight Head Major Diameter: Between 0.414 inches and 0.444 inches Grip Length: Any acceptable Heat Treatment: Annealed Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1011 or steel comp 1020 or steel comp 1021 or steel comp 1022 material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
| Between 0.135 inches and 0.151 inches Shank Diameter: Between 0.244 inches and 0.253 inches Shank Style: Straight Head Major Diameter: Between 0.414 inches and 0.444 inches Grip Length: Any acceptable Heat Treatment: Annealed Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1021 or steel comp 1022 Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
| Shank Diameter: Between 0.244 inches and 0.253 inches Shank Style: Straight Head Major Diameter: Between 0.414 inches and 0.444 inches Grip Length: Any acceptable Heat Treatment: Annealed Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1021 or steel comp 1022 Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
| Between 0.244 inches and 0.253 inches Shank Style: Straight Head Major Diameter: Between 0.414 inches and 0.444 inches Grip Length: Any acceptable Heat Treatment: Annealed Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1021 or steel comp 1021 or steel comp 1020 or steel comp 1021 or steel comp 1022 Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
| Shank Style: Straight Head Major Diameter: Between 0.414 inches and 0.444 inches Grip Length: Any acceptable Heat Treatment: Annealed Material: Steel comp 1005 or steel comp 1006 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1021 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
| Straight Head Major Diameter: Between 0.414 inches and 0.444 inches Grip Length: Any acceptable Heat Treatment: Annealed Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1021 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
| Head Major Diameter: Between 0.414 inches and 0.444 inches Grip Length: Any acceptable Heat Treatment: Annealed Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 102 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
| Between 0.414 inches and 0.444 inches Grip Length: Any acceptable Heat Treatment: Annealed Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
| Grip Length: Any acceptable Heat Treatment: Annealed Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
| Any acceptable Heat Treatment: Annealed Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
| Heat Treatment: Annealed Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
| Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
| Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
| Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
| or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
| Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | 013 |
| Material Specification: 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | ρ |
| 66 federal standard all material responses Surface Treatment: Any acceptable Shelf Life: N/a | |
| Surface Treatment: Any acceptable Shelf Life: N/a | |
| Any acceptable Shelf Life: N/a | |
| Shelf Life: N/a | |
| N/a | |
| | |
| | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A040a0 | |