

View Online at <https://aerobasegroup.com/nsn/5320-00-191-7371>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.520 inches and 0.545 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.044 inches and 0.056 inches

**Shank Diameter:**

0.2114 inches

**Shank Style:**

Pin-rivet, tapered, threaded

**Head Major Diameter:**

Between 0.312 inches and 0.323 inches

**Tip Diameter:**

0.2081 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

W/s: aircraft, (ac-130h, mc-130h, ec-130e, hc-130); aircraft, starlifter c-141; aircraft, stratofortress b-52; aircraft, hercules c-130

**Grip Length:**

Between 0.240 inches and 0.255 inches

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

1080000 single pounds per square inch

**Material:**

Steel comp 8740 or steel comp 4340

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0