NSN 5320-00-191-7371

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-191-7371



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.520 inches and 0.545 inches

Head Style:

Err-090

Head Height:

Between 0.044 inches and 0.056 inches

Shank Diameter:

0.2114 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.312 inches and 0.323 inches

Tip Diameter:

0.2081 inches

Lubrication:

Cetyl alcohol

End Application:

W/s: aircraft, (ac-130h, mc-130h, ec-130e, hc-130); aircraft, starlifter c-141; aircraft, stratofortress b-52; aircraft, hercules c-130

Grip Length:

Between 0.240 inches and 0.255 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

1080000 single pounds per square inch

Material:

Steel comp 8740 or steel comp 4340

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5320-00-191-7371

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

