## NSN 5320-00-195-1946

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-195-1946 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.740 inches and 0.760 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: Between 0.0635 inches and 0.0645 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.242 inches and 0.262 inches **Grip Length:** Between 0.433 inches and 0.443 inches **Thread Size:** 0.164 inches **Heat Treatment:** T-6 solution heat treated Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9, t6 federal specification single material response or qq-a-430, t6 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig: A528u0

No

## NSN 5320-00-195-1946

Pin-rivet - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.