

View Online at <https://aerobasegroup.com/nsn/5320-00-196-4688>

**Fastener Length:**

Between 0.528 inches and 0.558 inches

**Head Style:**

Hexagon

**Head Height:**

0.096 inches

**Shank Diameter:**

Between 0.163 inches and 0.165 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.407 inches and 0.469 inches

**Width Across Flats:**

Between 0.244 inches and 0.250 inches

**Hardness Rating:**

39.0 rockwell c nut and 43.0 rockwell c nut

**Shear Strength:**

3355 double pounds per square inch

**Material:**

Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve

**Material Specification:**

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve

**Surface Treatment:**

Cadmium sleeve and chromate sleeve and passivate sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response nut

**Specification Data:**

80205-nas1669 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5626 spec.