

View Online at <https://aerobasegroup.com/nsn/5320-00-199-2232>

Fastener Length:

0.406 inches

Head Style:

Universal

Head Height:

Between 0.080 inches and 0.090 inches

Shank Diameter:

Between 0.200 inches and 0.204 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.356 inches and 0.394 inches

Expansion Device:

Serrated stem-type w

End Application:

W/s: helicopter, carrier based asw, sh-60f; helicopter, mh-53e; helicopter, iroquois uh-1; hh-60l medivac; helicopter, seahawk, h-60; helicopter, electronic countermeasures, eh-60a; aircraft, airlifter c-17a; aircraft, stratofortress b-52; fms-a7 aircraft

Grip Length:

Between 0.126 inches and 0.187 inches

Shear Strength:

1210 single pounds per square inch

Material:

Nickel alloy r-405 locking ring or nickel alloy 400 locking ring

Material Specification:

Qq-n-281 federal specification all material responses locking ring

Surface Treatment:

Cadmium stem and chromate stem

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0