

View Online at <https://aerobasegroup.com/nsn/5320-00-199-2232>

**Fastener Length:**

0.406 inches

**Head Style:**

Universal

**Head Height:**

Between 0.080 inches and 0.090 inches

**Shank Diameter:**

Between 0.200 inches and 0.204 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.356 inches and 0.394 inches

**Expansion Device:**

Serrated stem-type w

**End Application:**

W/s: helicopter, carrier based asw, sh-60f; helicopter, mh-53e; helicopter, iroquois uh-1; hh-60l medivac; helicopter, seahawk, h-60; helicopter, electronic countermeasures, eh-60a; aircraft, airlifter c-17a; aircraft, stratofortress b-52; fms-a7 aircraft

**Grip Length:**

Between 0.126 inches and 0.187 inches

**Shear Strength:**

1210 single pounds per square inch

**Material:**

Nickel alloy r-405 locking ring or nickel alloy 400 locking ring

**Material Specification:**

Qq-n-281 federal specification all material responses locking ring

**Surface Treatment:**

Cadmium stem and chromate stem

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0