

View Online at <https://aerobasegroup.com/nsn/5320-00-205-7599>

**Head Style:**

Flush countersunk

**Shank Diameter:**

Between 0.374 inches and 0.375 inches

**Shank Style:**

Err-090

**Head Major Diameter:**

0.515 inches

**Grip Length:**

Between 0.626 inches and 0.688 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp e4340 or steel comp 4340 or steel comp 4037 or steel comp 4130

**Material Specification:**

Mil-s-6098 military specification 1st material response or mil-s-8503 military specification 2nd material response or mil-s-5626 military specification 3rd material response or mil-s-5000 military specification 4th material response or mil-s-5000 military specification 5th material response or mil-s-8695 military specification all material responses or mil-s-6758 military specification 6th material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6098 spec.