

View Online at <https://aerobasegroup.com/nsn/5320-00-205-7667>

**Head Style:**

Err-090

**Head Height:**

Between 0.068 inches and 0.078 inches

**Shank Diameter:**

0.312 inches

**Shank Style:**

Err-090

**Head Major Diameter:**

Between 0.475 inches and 0.505 inches

**Grip Length:**

Between 0.626 inches and 0.688 inches

**Features Provided:**

Casehardened

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Shear Strength:**

95000 single pounds per square inch

**Material:**

Steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 4130 or steel comp 6150 or steel comp 4037

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response or mil-s-8503 military specification 6th material response or mil-s-8695 military specification 7th material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Specification Data:**

80205-nas529 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.