NSN 5320-00-205-7810

Pin-rivet - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5320-00-205-7810

Head Style:

Err-090

Head Height:

Between 0.068 inches and 0.078 inches

Shank Diameter:

Between 0.312 inches and 0.313 inches

Shank Style:

Err-090

Head Major Diameter:

Between 0.475 inches and 0.505 inches

Grip Length:

Between 1.563 inches and 1.625 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 8735 or steel comp 8740 or steel comp 6150 or steel comp 4140 or steel comp e4340 or steel comp 4340 or steel comp 4037 or steel comp 4130

Material Specification:

Mil-s-6098 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-5626 military specification 4th material response or mil-s-5000 military specification 5th material response or mil-s-5000 military specification 6th material response or ams 6300 assn standard 7th material response or mil-s-6758 military specification 8th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

```
--
```

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6098 spec.

