

View Online at <https://aerobasegroup.com/nsn/5320-00-205-7896>

**Fastener Length:**

Between 0.446 inches and 0.466 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

Between 0.311 inches and 0.312 inches

**Shank Style:**

Err-090

**Head Major Diameter:**

Between 0.429 inches and 0.479 inches

**Grip Length:**

Between 0.189 inches and 0.250 inches

**Features Provided:**

Casehardened

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4130 or steel comp 4037

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-8503 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6049 military specification 4th material response or mil-s-6758 military specification 5th material response or mil-s-8695 military specification 6th material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Specification Data:**

80205-nas525 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.