## NSN 5320-00-205-7903

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-205-7903

| Fastener Length:   |
|--|
| Between 1.115 inches and 1.135 inches  |
| Head Style:  |
| Oval countersunk   |
| Shank Diameter:  |
| Between 0.155 inches and 0.159 inches  |
| Shank Style:   |
| Straight   |
| Head Major Diameter:   |
| Between 0.240 inches and 0.247 inches  |
| Grip Length:   |
| 0.891 inches   |
| Countersink Angle:   |
| Between 99.0 degrees and 101.0 degrees   |
| Material:  |
| Aluminum alloy 2117  |
| Material Specification:  |
| Qq-a-430 federal specification single material response  |
| Surface Treatment:   |
| Anodize or oxide film  |
| Surface Treatment Specification:   |
| Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response |
| Specification Data:  |
| 80205-nas1097 professional/industrial association standard   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A040a0   |
| Mil-std (military Standard):   |
| Mil-a-8625 spec.   |
|  |
|  |