

View Online at <https://aerobasegroup.com/nsn/5320-00-205-8548>

Fastener Length:

Between 0.928 inches and 0.948 inches

Head Style:

Err-090

Head Height:

Between 0.078 inches and 0.088 inches

Shank Diameter:

Between 0.374 inches and 0.375 inches

Shank Style:

Err-090

Head Major Diameter:

Between 0.565 inches and 0.600 inches

Grip Length:

0.688 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 4130 or steel comp 6150 or steel comp 4037 or steel comp 4130

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s05626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response or mil-s-8695 military specification 6th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Specification Data:

80205-nas529 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.