## NSN 5320-00-205-9583

Blind Rivet - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5320-00-205-9583                      |
|--|
| Fastener Length:   |
| Between 0.833 inches and 0.853 inches  |
| Head Style:  |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter:  |
| Between 0.383 inches and 0.386 inches  |
| Head Major Diameter:   |
| 0.566 inches   |
| Expansion Device:  |
| Drive stem-type h  |
| Grip Length:   |
| Between 0.728 inches and 0.790 inches  |
| Shear Strength:  |
| 75000 single pounds per square inch  |
| Countersink Angle:   |
| Between 99.0 degrees and 101.0 degrees   |
| Material:  |
| Steel comp 416 stem  |
| Material Specification:  |
| Qq-s-763 federal specification single material response stem                       |
| Surface Treatment:   |
| Cadmium  |
| Surface Treatment Specification:   |
| Qq-p-416, type 1, cl 3 federal specification single treatment response             |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A040a0   |
| Mil-std (military Standard):   |
| Mil-s-7720 spec.   |