

View Online at <https://aerobasegroup.com/nsn/5320-00-209-0148>

**Head Style:**

Hexagon

**Head Height:**

0.113 inches

**Shank Diameter:**

Between 0.1970 inches and 0.1990 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Threaded stem

**Grip Length:**

Between 0.595 inches and 0.656 inches

**Width Across Flats:**

Between 0.305 inches and 0.312 inches

**Material:**

Steel comp 4140 bolt or steel comp 8740 bolt or steel comp 303se boltsteel comp 4140 nut or steel comp 8740 nut or steel comp 303se nutsteel comp 303 sleeve or steel comp 304 sleeve or steel comp 303se sleeve

**Material Specification:**

Mil-s-5626 military specification 1st material response bolt or mil-s-6049 military specification 2nd material response bolt or mil-s-6758 military specification 3rd material response boltmil-s-5626 military specification 1st material response nut or mil-s-6049 military specification 2nd material response nut or mil-s-6758 military specification 3rd material response nutqq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

**Surface Treatment:**

Cadmium bolt and chromate boltcadmium nut and chromate nutpassivate sleeve and cadmium sleeve

**Surface Treatment Specification:**

Qq-p-416 ty ii cl 2 federal specification single treatment response boltqq-p-416 ty ii cl 2 federal specification single treatment response nutmil-s-5002 military specification 1st treatment response sleeve and qq-p-416 ty i cl 3 federal specification 2nd treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5626 spec.