NSN 5320-00-209-0187

Blind Rivet - Page 1 of 1



| view Online at https://aerobasegroup.com/nsn/5520-00-209-0167 |
|---|
| Fastener Length: |
| Between 0.606 inches and 0.636 inches |
| Head Style: |
| Hexagon countersunk |
| Head Height: |
| Between 0.072 inches and 0.079 inches |
| Shank Diameter: |
| Between 0.197 inches and 0.199 inches |
| Shank Style: |
| Threaded self-plugging shank w/sleeve |
| Expansion Device: |
| Serrated stem-type w |
| Lubrication: |
| Dry film or wax |
| Grip Length: |
| Between 0.406 inches and 0.469 inches |
| Width Across Flats: |
| Between 0.332 inches and 0.346 inches |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Shear Strength: |
| 3100 double pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel comp 4130 stem or steel comp 8740 stem or steel comp 4140 stem |
| Material Specification: |
| Qq-a-282 federal specification single material response body |
| Surface Treatment: |
| Cadmium stem |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response stem |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |

Mil-s-6758 spec.

Mil-std (military Standard):