# NSN 5320-00-209-3551

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-209-3551

## Fastener Length:

Between 0.490 inches and 0.510 inches

#### Head Style:

Undersized oval countersunk

# Head Height:

Between 0.004 inches and 0.006 inches

#### Shank Diameter:

Between 0.249 inches and 0.252 inches

#### Shank Style:

Straight

Head Major Diameter:

Between 0.371 inches and 0.395 inches

#### Head Minor Diameter:

Between 0.316 inches and 0.326 inches

#### **Countersink Height:**

0.060 inches

#### Shear Strength:

24000 single pounds per square inch

#### **Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

#### Material:

Aluminum alloy 5056

#### Surface Treatment:

Anodize or chromate

## Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

#### **Specification Data:**

80205-nas1097 professional/industrial association standard

#### Shelf Life:

N/a

## Unit Of Measure:

```
---
```

# Demilitarization:

No

## Fiig:

A040a0

# Mil-std (military Standard):

Mil-a-8625 spec.