
# NSN 5320-00-215-0453

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Identification Code Color:

Bronze

#### Fastener Length:

Between 1.865 inches and 1.885 inches

#### Head Style:

Err-090

Head Height:

Between 0.068 inches and 0.078 inches

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3110 inches and 0.3120 inches

Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.475 inches and 0.505 inches

Grip Length:

1.380 inches

#### Min. Tensile Strength (psi):

160000 pounds per square inch

**Thread Size:** 

0.312 inches

#### Shear Strength:

95000 single pounds per square inch

#### Material:

Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740

## Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5626 military

specification 3rd material response or mil-s-6049 military specification 4th material response

# Surface Treatment:

Cadmium

# Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

# Thread Series Designator:

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

# NSN 5320-00-215-0453

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

