# NSN 5320-00-218-8207

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-218-8207

## Fastener Length:

0.662 inches

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.189 inches and 0.193 inches

## Shank Style:

Self-plugging mechanically locked stem

## Head Major Diameter:

Between 0.349 inches and 0.357 inches

## **Expansion Device:**

Serrated stem-type w

## Grip Length:

Between 0.438 inches and 0.500 inches

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

## Material:

Aluminum alloy 5056 sleeve

## **Material Specification:**

Qq-a-430 federal specification single material response stem

## Surface Treatment:

Anodize stem or chromate stem

## Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response stem or mil-c-5541 military specification 2nd treatment response stem

## **Specification Data:**

80205-nas1921 professional/industrial association standard

#### Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A040a0

## Mil-std (military Standard):

Mil-a-8625 spec.