NSN 5320-00-223-0363



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-00-223-0363 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.933 inches and 1.958 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.3547 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.472 inches and 0.522 inches **Tip Diameter:** 0.3254 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.552 inches and 1.567 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.3254 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Slot included Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 assn standard 1st material response or mil-s-6049 assn standard 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

--

N/a

Unit Of Measure:

NSN 5320-00-223-0363

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.