

View Online at <https://aerobasegroup.com/nsn/5320-00-231-3663>

Fastener Length:

Between 0.459 inches and 0.499 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.246 inches and 0.252 inches

Shank Style:

Drive pin

Head Major Diameter:

Between 0.472 inches and 0.480 inches

Expansion Device:

Drive stem-type h

Grip Length:

Between 0.297 inches and 0.359 inches

Hardness Rating:

95.0 rockwell b body

Countersink Angle:

Between 98.0 degrees and 102.0 degrees

Material:

Steel comp 301 stem or steel comp 302b stem or steel comp 302 stem or steel comp 303 stem or steel comp 303se stem or steel comp 304 stem or steel comp 304l stem or steel comp 305 stem or steel comp 308 stem or steel comp 309 stem or steel comp 309s stem or steel comp 310 stem or steel comp 310s stem or steel comp 314 stem or steel comp 316 stem or steel comp 316l stem or steel comp 317 stem or steel comp 321 stem or steel comp 347 stem or steel comp 348 stem or steel comp 384 stem or steel comp 385 stem or steel stem

Material Specification:

G66 federal standard all material responses body

Surface Treatment:

Passivate stem

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0