

View Online at <https://aerobasegroup.com/nsn/5320-00-233-3284>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.223 inches and 1.243 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.120 inches and 0.130 inches

**Width Between Flats:**

0.156 inches

**Shank Diameter:**

Between 0.3735 inches and 0.3745 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.530 inches and 0.565 inches

**Grip Length:**

Between 0.683 inches and 0.693 inches

**Features Provided:**

Washer

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.375 inches

**Special Features:**

0.622 in. To 0.628 in. Collar o/d

**Material:**

Steel comp 4130 or steel comp 4140 or steel comp 8740

**Material Specification:**

Mil-s-6758 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6758 spec.