NSN 5320-00-233-4768

Solid Rivet - Page 1 of 1

Mil-a-8625 spec.



View Online at https://aerobasegroup.com/nsn/5320-00-233-4768

| Fastener Length: |
|--|
| Between 1.490 inches and 1.510 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.311 inches and 0.315 inches |
| Shank Style: |
| Straight |
| Head Major Diameter: |
| Between 0.560 inches and 0.568 inches |
| Grip Length: |
| Between 1.021 inches and 1.041 inches |
| Shear Strength: |
| 26000 single pounds per square inch |
| Countersink Angle: |
| Between 99.5 degrees and 100.5 degrees |
| Material: |
| Aluminum alloy 2117 |
| Material Specification: |
| Qq-a-430 federal specification single material response |
| Surface Treatment: |
| Anodize or oxide film |
| Surface Treatment Specification: |
| Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |